


HS2V H01 SERIES

Current Sensor

Model Number

HS2V 200 H01
HS2V 300 H01
HS2V 400 H01
HS2V 500 H01
HS2V 600 H01
HS2V 800 H01
HS2V 1000 H01
HS2V 1200 H01
HS2V 1500 H01



For the electronic measurement of current: DC, AC, pulsed..., with galvanic insulation between the primary and the secondary circuits.

Features

- ✧ Open loop current sensor using the Hall effect
- ✧ Galvanic insulation between primary and secondary
- ✧ Insulating plastic case recognized according to UL 94-V0
- ✧ No insertion losses
- ✧ Small size
- ✧ Standards:
 - IEC 60664-1:2020
 - IEC 61800-5-1:2022
 - IEC 62109-1:2010

Applications

- ✧ AC variable speed
- ✧ Uninterruptible Power Supply (UPS)
- ✧ Static converters for DC motor drives
- ✧ Switch Mode Power Supplies (SMPS)
- ✧ Power supplies for welding applications
- ✧ Battery management
- ✧ Wind energy inverter

Safety

This sensor must be used according to IEC 61800-5-1

This sensor must be used in electric/electronic equipment with respect to applicable standards and safety requirements in accordance with the following manufacture's operating instructions.

Caution, risk of electrical shock!



When operating the sensor, certain parts of the module can carry hazardous voltage (e.g., Primary busbar, power supply). Ignore this warning can lead to injury and/or cause serious damage.

This sensor is a built-in device, whose conducting parts must be inaccessible after installation. A protective housing or additional shield could be used.

Main supply must be able to be disconnected.

HS2V H01 SERIES

Absolute maximum ratings(not operating)

Parameter	Symbol	Unit	Value
Supply voltage	V_C	V	± 15.75
Primary conductor temperature	T_B	°C	105
ESD rating, Human Body Model (HBM)	V_{ESD}	kV	4

- ✗ Stresses above these ratings may cause permanent damage.
- ✗ Exposure to absolute maximum ratings for extended periods may degrade reliability.

Environmental and mechanical characteristics

Parameter	Symbol	Unit	Min	Typ	Max	Comment
Ambient operating temperature	T_A	°C	-40		105	
Ambient storage temperature	T_S	°C	-45		110	
Mass	m	g		310		

Insulation coordination

Comment

Parameter	Symbol	Unit	Value	
Rms voltage for AC insulation test @ 50Hz, 1min	V_d	kV	2.3	
Impulse withstand voltage 1.2/50 μ s	V_w	kV	4.3	
Clearance (pri.- sec.)	d_{CI}	mm	7.1	
Creepage distance (pri.- sec.)	d_{CP}	mm	15.1	
Plastic case	-	-	UL94-V0	
Comparative tracking index	CTI	PLC	Group IIIa	
Application example	-	-	300V	Reinforced insulation, according to IEC 61800-5-1, IEC 62109-1
Application example	-	-	600V	Basic insulation, according to EC 61800-5-1, IEC 62109-1

HS2V H01 SERIES


Electrical data

※ With $T_A = 25^\circ\text{C}$, $V_C = \pm 15\text{V}$, $R_L = 10\text{k}\Omega$, unless otherwise noted.

Parameter	Symbol	Unit	Min	Typ	Max	Comment
Primary nominal rms current	I_{PN}	A	-200		200	HS2V 200 H01
			-300		300	HS2V 300 H01
			-400		400	HS2V 400 H01
			-500		500	HS2V 500 H01
			-600		600	HS2V 600 H01
			-800		800	HS2V 800 H01
			-1000		1000	HS2V 1000 H01
			-1200		1200	HS2V 1200 H01
			-1500		1500	HS2V 1500 H01
Primary current, measuring range	I_{PM}	A	-600		600	HS2V 200 H01
			-900		900	HS2V 300 H01
			-1200		1200	HS2V 400 H01
			-1500		1500	HS2V 500 H01
			-1800		1800	HS2V 600 H01
			-2400		2400	HS2V 800 H01
			-2500		2500	HS2V 1000...1500 H01
Supply voltage	V_C	V		± 15		@ 5%
Supply current	I_C	mA		20		
Load resistance	R_L	k Ω	10			
Output voltage (Analog) @ I_{PN}	V_{OUT}	V	± 3.980	± 4.000	± 4.020	
Electrical offset voltage	V_{OE}	mV	-20		20	
Temperature coefficient of V_{OE}	TCV_{OE}	mV/K	-0.5		0.5	@ $-40^\circ\text{C} \sim 105^\circ\text{C}$
Theoretical sensitivity	G_{th}	mV/A		20.00		HS2V 200 H01
				13.33		HS2V 300 H01
				10.00		HS2V 400 H01
				8.00		HS2V 500 H01
				6.67		HS2V 600 H01
				5.00		HS2V 800 H01
				4.00		HS2V 1000 H01
				3.33		HS2V 1200 H01
				2.67		HS2V 1500 H01
Sensitivity error	ε_G	%		± 0.5		Exclusive of V_{OE}
Temperature of G	TCG	%/K	-0.05		0.05	@ $-40^\circ\text{C} \sim 105^\circ\text{C}$
	ε_L	% of I_{PN}	-1		1	Exclusive of V_{OE}
Hysteresis offset voltage@ $p=0$ after $1 \times I_{PN}$	V_{OM}	mV	-10		10	
Accuracy@ I_{PN}	X	% of I_{PN}	-1		1	Exclusive of V_{OE}
Response time@90% of I_{PN}	t_r	μs			5	
Frequency bandwidth(-3dB)	BW	kHz	25			

HS2V H01 SERIES

Dimensions (in mm. 1 mm = 0.0394 inch)



Mechanical characteristic

- General tolerance: ± 0.5 mm
- Connection of secondary: RVVP 4x0.3mm² Shielded wire
- Output line length: 1500 $\pm$ 20mm
- Primary hole: 40.5mmx32.5mm
- Sensor: 2pc $\Phi 4.5$ mm through hole
2pc M4 Metal screws

Recommended fastening torque 2.1 N•m ($\pm 10\%$)

Remarks

- V_{OUT} and I_P are in the same direction, when I_P flows in the direction of arrow.
- Temperature of primary conductor should not exceed 105°C.
- Dynamic performances (di/dt and response time) are best with a single bar completely filling the primary hole.

This is a standard model. For different applications (measurement, secondary connections...), please contact CHIPSENSE.